




















# 2000 PUR

Attractive, high performance, heavy duty homogeneous sheet and tile floor covering with a polyurethane reinforcement for low cost, lifetime polish free maintenance.

Featuring a directional duotone marbleised decoration, with marbleised highlight tones, 2000 PUR is available in a broad palette of vibrant shades. Demonstrating outstanding durability and abrasion resistance, 2000 PUR is recommended for use throughout commercial interiors, healthcare and education facilities, as well as retail outlets.



	<b>Gauge</b>	EN 428/ISO 24346	2.0mm 2.5mm
	<b>Roll Size</b>	EN 426/ISO 24341	2.0mm: 2m x 20m = 40m <sup>2</sup> 2.5mm: 2m x 15m = 30m <sup>2</sup>
	<b>Tile Size</b>	EN 427/ISO 24342	2.0mm: 300mm x 300mm = 4.5m <sup>2</sup> 2.0mm: 608mm x 608mm = 5.17m <sup>2</sup> 2.5mm: 300mm x 300mm = 3.6m <sup>2</sup>
	<b>Total Weight</b>	EN 430/ISO 23997	2.0mm: 3550g/m <sup>2</sup> 2.5mm: 4552g/m <sup>2</sup>
	<b>General Performance</b>	EN 649/EN ISO 10581 ASTM F1913 ASTM F1700	Conforms Conforms Conforms
	<b>Use Area</b>	EN 685/ISO 10874	  
	<b>Reaction to Fire</b>	EN 13501-1 ASTM E662* ASTM E648* CAN/ULC S102.2*	Class Bfl-S1 <450 Class 1 FSV < 300, SDV <500 *2.0mm
	<b>Abrasion Resistance</b>	EN 660-2	Group M
	<b>Binder Content</b>	EN ISO 10581	Type II
	<b>Slip Resistance</b>	EN 13893 AS 4586	Class DS R9
	<b>Indentation Residual</b>	ASTM F970 (Modified)	Static load 750psi
	<b>Electrical behaviour (body voltage)</b>	EN 1815	≤2kV Classified as 'antistatic'
	<b>Castor Chair (continuous use)</b>	EN 425/ISO 4918	Suitable
	<b>Maritime Usage</b>	American Bureau of Shipping* US Coast Guard Approved* Marine Equipment Directive 2014/90/EU* SOLAS 74*	Conforms Conforms Conforms Conforms *2.0mm
	<b>VOC Emissions</b>	Indoor Air Comfort GOLD AgBB VOC test Floorscore Finnish M1 Classification* GBCA/NZGBC Green Star IEQ-VOC	Eurofins certified product Pass Certified Certified Compliant *2.0mm
	<b>Responsible Sourcing</b>	BES 6001	Excellent
	<b>Environmentally Preferable Flooring</b> - Polyflor 2000 PUR* achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 472) in major use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Gold Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. Polyflor 2000 PUR is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit <a href="http://www.polyflor.com/sustainability">www.polyflor.com/sustainability</a> . *2.0mm		
	<b>PUR</b> - Polyflor 2000 PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost, polish free maintenance regime for the lifetime of the flooring.		
	<b>Hygiene</b> - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.		
	Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult <b>Polyflor Customer Technical Services</b> on +44 (0)161 767 1912, or email <a href="mailto:tech@polyflor.com">tech@polyflor.com</a> . The data presented is correct at the time of printing. For latest information, please visit our website <a href="http://polyflor.com">polyflor.com</a> . Decoration and shade may vary slightly from the samples shown.		

